

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

1.Data Sheet

RF Cable Assembly Specification

主要技术指标		Main technical specifications	
频率范围 (MHZ)	0~3000	Frequency Range (MHZ)	0~3000
特性阻抗(Ω)	50	Impedance(Ω)	50
输出电压 驻波比	<2.0	VSWR	<2.0
插损(dB)	<2.0	Insertion Loss(dB)	<2.0
物理性能		Physical Properties	
线材	1.13 同轴线	Cable	1.13 Coaxial
连接头	SMA +IPEX	Connector	SMA +IPEX
保存温度	-30℃~+75℃	Storage Temp	-30℃~+75℃
工作温度	-20℃~+65℃	Operating Temp	-20℃~+65℃

2.Testing Report

Frequency	1GHz	2GHz	3GHz
S11 Swr Test(dB)	1.03	1.06	1.08
S22 Swr Test(dB)	1.05	1.12	1.16
S21 Log Mag Test(dB)	-0.15	-0.32	-0.41

TEL: 86-371-58561629

Email: info@global-antenna.com

Add: Room 1124, BLDG C,Chaoliumao,High-Tech Zone,Zhengzhou,China,Zip: 450001

3.Outline Drawing:

